

Standard triple punched Verizon IoT SIM



Hardware Features

Operating Characteristics

- Voltage:
Class A, B, C (1.8V – 5.0V ±10%)
- Temperature Range:
-25 to + 85 °C

CPU

- 32-bit CPU core

Memory

- 340 - 480 kB Flash
- 10 - 13 kB RAM
- Min. 100,000 erase/write cycles for page at room temperature
- Data retention of 25 years at room temperature

Serial I/O

- Hardware UART (conforms to ISO7816)

DES

- Built-in hardware DES/TDES

Other Chip Features

- 16-bit random number generator (RNG)
- Parity calculator for 8/16/32 bit CRC-16/32 calculator
- 16-bit programmable interval timers
- Dividers: 8, 16, 32, 64, 372
- Form factors: ID-1, 2FF (Standard SIM), 3FF (Micro SIM), 4FF (Nano SIM), Triple SIM

Software Features

Key Features

- Release 12 LTE
- 2G / 3G / LTE / CDMA
- Milenage, TUAK, COMP 128-1/2/3/4, CAVE
- DPA-/SPA-resistant
- DES, AES, SHA 1/256-Hashing, MD5
- Protocols: T=0 / T=1
- Java Card: 3.0.1
- Java™ API:
 - UICC and USAT API
 - Smart de-fragmentation
 - Support of Integer for Java
- GP 2.2.1:
 - GP Key Management
 - GP SD and Hierarchy
 - GP Card Life Cycle States
- OTA Rel. 9+:
 - OTA via SMS / HTTPs / BIP CAT-TP
 - Remote File Management (RFM)
 - Remote Applet Management (RAM)
- Browsers: WIB 1.3 / WIB 2.0 / S@T v4
- R-UIM / CSIM
- ISIM / GBA
- EAP AKA / EAP SIM
- ProSe
- GeoLocation API Rel. 13
- Enhanced Administrative Commands
- Enhanced memory management for 3rd party applications
- Intelligent memory management system to enhance erase/ write cycles



Key Standard Compliance

ETSI

- 101 220 ETSI numbering system for telecommunication application providers
- 102 127 Transport protocol for CAT applications Stage 2
- 102 221 UICC-Terminal interface; Physical and logical characteristics
- 102 222 Administrative commands for telecommunications applications
- 102 223 Card Application Toolkit (CAT)
- 102 225 Secured packet structure for UICC based applications
- 102 226 Remote APDU structure for UICC based applications
- 102 241 UICC Application Programming Interface (API) for Java Card
- 102 268 Test specification for UICC Application Programming Interface (API) for Java Card

3GPP

- 43.019 Subscriber Identity Module Application Programming Interface (SIM API) for Java Card Stage 2
- 51.011 Specification of the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface
- 51.013 Test specification for Subscriber Identity Module (SIM) Application Programming Interface (API) for Java Card
- 51.014 Specification of the SIM Application Toolkit for the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface
- 51.017 Subscriber Identity Module (SIM) conformance test specification
- 31.048 Security mechanisms for the (U)SIM application toolkit; Test specification
- 31.101 UICC-Terminal Interface; Physical and Logical Characteristics
- 31.102 Characteristics of the USIM Application
- 31.103 Characteristics of the IP Multimedia Services Identity Module (ISIM) application
- 31.111 USIM Application Toolkit (USAT)
- 31.115 Secured packet structure for (U)SIM Toolkit applications
- 31.116 Remote APDU Structure for (U)SIM Toolkit applications
- 31.122 USIM conformance test specification
- 31.130 (U)SIM API for Java Card
- 31.213 Test Specification: Application Programming Interface (API) for Java Card
- 31.900 SIM/USIM Internal and External Interworking Aspects
- 31.919 2G/3G Java Card
- API based applet interworking

3GPP2

- C.S0016-C Over-the-Air Service Provisioning of Mobile Stations in Spread Spectrum Standards, Rev.C V2.0
- C.S0023-C Removable User Identity Module for Spread Spectrum Systems, Rev.C V2.0
- C.S0035 CDMA Card Application Toolkit (CCAT), Rev.A V1.0
- C.S0065-A CDMA2000 Application on UICC for Spread Spectrum Systems, Rev.A V1.0

Sun/Oracle Specifications

- JCRE 2.1.1 Java Card 2.1.1 Runtime Environment (JCRE) Specification, Rev. 1.0
- JCRE 2.2.2 Runtime Environment Specification, Java Card Platform, V2.2.2
- JCVM 2.2.2 Virtual Machine Specification, Java Card Platform, V2.2.2
- JCAPI 2.2.2 Application Programming Interface, Java Card Platform, V2.2.2

Global Platform Specifications

- GlobalPlatform Card Specification, V2.1.1
- GP 2.2 AmdB Remote Application Management over HTTP, Card Specification V2.2 - Amendment B, V1.1

All SIM specifications provided Glesecke+Devrient